Product Specification *AddKan* Masterbatch

UV MASTERBATCH 20 AD/01/0044

This is a very special UV masterbatch with 20% effective active content of HALS stabilizer. Indicative addition levels are in the range of 1-3% based on UV exposure and the end product thickness Protect the polymer from losing the mechanical properties by preventing light and oxygen decomposition without affecting the appearance. Combination of radical interceptors with specialty additives, manufactured using modern compounding techniques imparts uniform dispersion and a very effective product. Specially designed for Monolayer & Multi Layer application.

	0	
Typical Properties	Typical Values	Units
Physical		
Moisture Content	< 0.1	%
Heat Stability	260-280	ō C
Food contact	Yes	
Carrier Resin	Polyethylene	
Applications		
Monolayer & Multi layer Film Extrusion		

All the above values are obtained under standard conditions with our testing facilities, may vary under different conditions and depending upon the accuracy and efficiency of the man and the machine. So it's recommended to test the above properties to finalize the use of the product for specific and particular applications. The information regarding the minerals is based on the test results and reports provided by the supplier.

OFFICE: Plot No.112, Minerva Industrial Estate, P.K.Road, Nr Hercules Hoist, Mulund (W)

Mumbai-400080, INDIA Tel: 022-61510500 Fax: 022-25916269

E-mail: masterbatchinfo@kandui.in_URL: www.additivemasterbatches.com